

_ProfileInfoExtensions

StatisticalInfos

Element @Attribute	Type	Num	Description	Comments + Contents Outbound	pAir	OnPrem	Comments + Contents Inbound	pAir	OnPrem
px:ProfileInfoExtensions		0..1	A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).		✓	✓		✗	✗
px:ProfileInfoExtensions Traces Trace		0..1	Profile-level trace messages.		✓	✓		✗	✓
@TraceBegin	dateTime	0..1	Trace scheduled begin datetime		✓	✓		✗	✓
@TraceEnd	dateTime	0..1	Trace scheduled end datetime		✓	✗		✗	✗
@TraceDepartment	StringLength1to255	0..1	Department Trace was defined to action the trace		✓	✓		✗	✓
px:ProfileInfoExtensions px:DocumentTypes px:DocumentType					✓	✗		✗	✗
@DefaultInd	boolean	0..1		"true" "false"	✓	✗		✗	✗
@DisplaySequence	StringLength1to32		Display sequence		✓	✗			
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellIO) and inbound (to protellIO) request messages, this must carry the string value	"protellIO"	✓	✗		✗	✗
@Type	StringLength1to32	0..1	The type indicates what the document is called in the PMS		✓	✗		✗	✗
@RPH	string	0..1	Internal Reference		✓	✗		✗	✗
@ID	string	0..1	Internal Reference		✓	✗		✗	✗
px:ProfileInfoExtensions px:AddressTypes px:AddressType		0..1	Additional Address Information		✓	✗		✗	✗
@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the address is the primary for the profile.		✓	✗		✗	✗
@ID	string	0..1	Internal Reference		✓	✗		✗	✗
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellIO) and inbound (to protellIO) request messages, this must carry the string value		✓	✗		✗	✗
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✗		✗	✗
@Type	StringLength1to32	0..1	The type of the additional address Information		✓	✗		✗	✗
px:ProfileInfoExtensions px:Salutation		0..1	The Salutation is used in the profile.		✓	✓		✗	✓

@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the salutation is the primary for the profile.	"true" "false"	✓	✗		✗	✗
@ID	string	0..1	Internal Reference		✓	✓		✗	✓
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellO) and inbound (to protellO) request messages, this must carry the string value	"protellO"	✓	✓		✗	✓
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✗		✗	✗
@Type	StringLength1to32	0..1	The type of the Salutation information	SALUTATION	✓	✓		✗	✓
px:ProfileInfoExtensions px:StatisticalInfos		0..1			✗	✓		✗	✗
@Source	string	0..1	Sales source of guest		✗	✓		✗	✗
@StatisticalRegion	string	0..1			✗	✓		✗	✗
px:ProfileInfoExtensions px:StatisticalInfos ParentProfile		0..1	Information about the master profile attached to this profile		✓	✓		✓	✗
@Name	StringLength1to255	0..1	Name		✓	✓		✓	✗
@ID	string	0..1	Profile ID of master account		✓	✓		✓	✗
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellO) and inbound (to protellO) request messages, this must carry the string value	"protellO"	✓	✓		✓	✗
@Type	OTA_CodeTypePRT	0..1	Numeric reference to the type of profile such as guest, company, agent etc. Refer to the OTA Code Lists: Profile Type (PRT)	Profile Type (PRT)	✓	✓		✓	✗
px:ProfileInfoExtensions px:AccountingInfos			Accounting Infos		✓	✓	In order to be possible all operations (delete, update, insert, leave as it is) implementation will have the following logic: If AccountingInfos not set (null) - we leave all data as it is. If AccountingInfos.@Tax1(Tax2) field is blank (spaces /empty -no literal/number/special chars) we delete field data. If AccountingInfos.@Tax1(Tax2) field is not set (null) will leave field as it is. If AccountingInfos.@Tax1(Tax2) has any letters/numbers /special characters we override (insert) value.	✓	✓
@Tax1	StringLength1to32	0..1	for company		✓	✓		✓	✓
@Tax2	StringLength1to32	0..1	for distribution partner		✓	✓		✓	✓
@PublicAdministrationInd	boolean	0..1	Used to identify if the profile is a Public Administration	"true" "false"	✓	✗		✓	✗

@SplitPaymentInd	boolean	0..1	Used to identify if the profile is allowed to use Split Payment	"true" "false"	✓	✗		✓	✗
@FiscalUID	string	0..1	UID Number		✓	✗		✓	✗
@CompanyRegNumber	string	0..1	Company Registration Number		✓	✗		✓	✗
px:ProfileInfoExtensions px:Memberships		0..1	This path enables to add additional information to specific IDs linked to the guest profile.		✓	✓		✓	✓
px:ProfileInfoExtensions px:Memberships px:Membership		0..n	This path enables to add additional information to specific IDs linked to the guest profile.		✗	✓	OnPrem: For each <Membership> element a corresponding <CustLoyalty> element needs to be send, otherwise the membership data is not updated.	✗	✓
@ID	string	0..1	Internal Reference		✗	✓		✗	✓
@RPH	string	0..1	Internal Reference		✗	✓		✗	✓
@Type	StringLength1to32	0..1	The type of the Membership Information		✗	✓		✗	✓
@CardHolderName	string	0..1	Name of the Membership card		✗	✓		✗	✓
@EnrollmentAt	StringLength1to255	0..1	Location of the Enrollment		✗	✓		✗	✓
@EnrollmentCode	StringLength1to255	0..1	Internal Code of the Location of the Enrollment		✗	✓		✗	✓
@EnrollmentSource	StringLength1to255	0..1	Source of the Location of the Enrollment		✗	✓		✗	✓
@InactivationDate	date	0..1	Inactive Date of the Membership		✗	✓		✗	✓
px:ProfileInfoExtensions px:ContactDetails AdditionalInfo px:Entry		0..n	Contact Information		✓	✗		✗	✗
@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the phone number is the primary phone number for the profile.	- true - false	✓	✗		✗	✗
@ID	string	0..1	Internal Reference		✓	✗		✗	✗
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellIO) and inbound (to protellIO) request messages, this must carry the string value	"protellIO"	✓	✗		✗	✗
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✗		✗	✗
@Type	StringLength1to32	0..1	The type of the additional Contact Information	CONTACTTYPE	✓	✗		✗	✗
px:ProfileInfoExtensions px:PersonInfos		0..1	Additional Person Information		✓	✗		✗	✗
px:ProfileInfoExtensions px:PersonInfos px:LastNameAtBirth	string	0..1	Information about the lastname at birth		✓	✗		✓	✗
px:ProfileInfoExtensions px:PersonInfos px:FirstNameAtBirth	string	0..1	Information about the given name at birth		✓	✗		✓	✗

px:ProfileInfoExtensions px:PersonInfos px:LastNameMother	string	0..1	Information about the mother's lastname		✓	✗		✓	✗
px:ProfileInfoExtensions px:PersonInfos px:FirstNameMother	string	0..1	Information about the mother's given name		✓	✗		✓	✗
px:ProfileInfoExtensions px:PersonInfos px:Language		0..1	The language code for which the name data is represented. While this value is optional, it is HIGHLY RECOMMENDED that it be used.		✓	✓		✗	✗
@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the language is the primary for the profile.		✓	✓		✗	✗
px:ProfileInfoExtensions px:PersonInfos px:Vipcodes		0..1	VIP Codes of the guest.		✓	✓		✗	✓
px:ProfileInfoExtensions px:PersonInfos px:Vipcodes px:Code		1..n	A string reference representing a Vip code of the guest.		✓	✓		✗	✓
@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the VIP code is the primary for the profile.	"true" "false"	✓	✓	OnPrem: Only primary VIP code can be updated.	✗	✓
@ID	string	0..1	Internal Reference		✓	✓		✗	✓
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protello) and inbound (to protello) request messages, this must carry the string value	"protello"	✓	✓		✗	✓
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✓		✗	✓
@Type	StringLength1to32	0..1	Type of the code	"VIPCODE"	✓	✓		✗	✓
px:ProfileInfoExtensions px:PersonInfos px:MarketingCodes		0..1	Marketing Codes of the guest.		✓	✓		✗	✓
px:ProfileInfoExtensions px:PersonInfos px:MarketingCodes px:Code		1..n	A string reference representing the Marketing Code of the guest.		✓	✓		✗	✓
@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the marketing code is the primary for the profile.	"true" "false"	✓	✓		✗	✓
@ID	string	0..1	Internal Reference		✓	✓		✗	✓
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protello) and inbound (to protello) request messages, this must carry the string value	"protello"	✓	✓		✗	✓
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✓		✗	✓
@Type	StringLength1to32	0..1	Type of the code	"MARKETINGCODE"	✓	✓		✗	✓
px:ProfileInfoExtensions px:PersonInfos px:Keywords		0..1	Keywords of the guest.		✓	✗		✗	✗
px:ProfileInfoExtensions px:PersonInfos px:Keywords px:Code		1..n	A string reference representing the Keywords of the guest.		✓	✗		✗	✗

@DefaultInd	boolean	0..1	A boolean value is used to indicate whether the keyword is the primary for the profile.	"true" "false"	✓	✗		✗	✗
@ID	string	0..1	Internal Reference		✓	✗		✗	✗
@ID_Context	StringLength1to32	0..1	Used to identify the source of the identifier. For both outbound (from protellO) and inbound (to protellO) request messages, this must carry the string value	"protellO"	✓	✗		✗	✗
@DisplaySequence	StringLength1to32	0..1	Display sequence		✓	✗		✗	✗
@Type	StringLength1to32	0..1	Type of the code	"KEYWORD"	✓	✗		✗	✗
px:ProfileInfoExtensions px:PersonInfos px:Registration		0..1	A string reference represents the registration.		✓	✓		✗	✓
@BirthDate	string	0..1	Birth date of the guest		✓	✗	If both attributes Customer@BirthDate and Registration/@BirthDate are given with valid values, the value from Registration/@BirthDate will be taken	✓	✗
@BirthPlace	string	0..1	Place of birth of the guest		✓	✓		✓	✓
@BirthCountry	string	0..1	Country of birth of the guest	"DE" ISO 2 code	✓	✓		✓	✓
px:ProfileInfoExtensions px:PersonInfos px:Registration px:Occupation	string	0..1	Occupation of the guest		✓	✓		✗	✗
px:ProfileInfoExtensions px:PersonInfos px:Registration px:LicensePlate	string	0..1	The License plate number of the guest's car registration.		✓	✓		✓	✓
px:ProfileInfoExtensions px:PersonInfos px:Registration px:DocumentInfos px:DocumentInfo		0..1	Additional document information		✓	✓		✓	✓
@ID	string	0..1	Internal Reference		✓	✓		✓	✓
@ID_Context	StringLength1to32	0..1	Information about additional document number type	"SNDS" = Spanish Numero de Soporte "SNIE" = Spanish Número de identidad de extranjero	✓	✓		✓	✓
@RPH	string	0..1	Internal reference to a document in .. Customer Document		✓	✓		✓	✓
@Type	StringLength1to32	0..1	type of document	"DocumentIdentifier"	✓	✓	"DocumentIdentifier"	✓	✓